

MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: H 901 A GENERAL USE: Cleaning solvent PRODUCT DESCRIPTION: Colorless flammable liquid	
--	---

MANUFACTURER'S NAME Dysol Inc. (formerly Dynamold Solvents, Inc.) ADDRESS (NUMBER, STREET, P.O. BOX) 2901 Shamrock Avenue Fort Worth, TX 76107	DATE PREPARED: November 3, 2006 SUPERSEDES: September 1, 2006 TELEPHONE NUMBER FOR INFORMATION (817) 335-1826 EMERGENCY TELEPHONE NUMBER CHEM • TEL (800) 255-3924 Outside USA (813) 248-0585	Page 1 of 4
DISTRIBUTOR'S NAME ADDRESS (NUMBER, STREET, P.O. BOX) (CITY, STATE AND ZIP CODE)	TELEPHONE NUMBER FOR INFORMATION EMERGENCY TELEPHONE NUMBER	

SECTION 2 - HAZARDOUS INGREDIENTS

HAZARDOUS COMPONENTS	CAS #	% (by weight)	OSHA PEL		ACGIH TWA		SARA TITLE III	RQ LBS
			PPM	MG/M3	PPM	MG/M3		
Toluene (a,b,c,d,e)	108-88-3	25	200		50		Yes	1000
Petroleum distillate, aliphatic	64742-89-8	25	100	500				
Ethyl acetate (a,b,c)	141-78-6	20	400	1400	400		Yes	5000
Methyl ethyl ketone (a,b,c)	78-93-3	10	200	590	200		Yes	5000
Isopropyl alcohol	67-63-0	10	400	980	400			
Acetone (b,c)	67-64-1	10	1000	2400	500			5000

(a,c) See Section 15

(b) Indicates that the Resource Conservation and Recovery Act (RCRA) has determined the waste for this chemical is listed as hazardous and must be handled according to regulations in 40 CFR 260-281.

(d) Indicates listing in Table Z - 2, 29 CFR 1910.1000, value shown is 8-hour Time Weighted Average. See table for acceptable ceiling concentration limits and acceptable maximum peak above the acceptable ceiling concentration.

(e) California Prop 65, Safe Drinking Water and Toxic Enforcement Act of 1986, chemicals known to the state to cause cancer or reproductive toxicity. A person in the course of doing business must warn others who may consume, come into contact with, or otherwise be exposed to this chemical.

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Colorless highly flammable liquid, hazardous vapors. Can cause serious or fatal complications if swallowed. Can cause eye and skin irritation upon contact. Inhalation of vapors can cause anesthetic effect leading to death in poorly ventilated areas.

POTENTIAL HEALTH EFFECTS

INHALATION: High concentrations are irritating to the respiratory tract; may cause headache, dizziness, nausea, vomiting and malaise.

SKIN: Brief contact may cause slight irritation; prolonged contact may cause moderate irritation or dermatitis.

EYES: High vapor concentration or contact may cause irritation and discomfort.

INGESTION: May result in vomiting; aspiration of vomitus into the lungs must be avoided; DO NOT induce vomiting. Minute amounts aspirated into the lungs can produce severe lung injury, chemical pneumonitis, pulmonary edema or death.

CARCINOGENICITY	NTP?	No	IARC MONOGRAPHS?	No	OSHA REGULATED?	No
-----------------	------	----	------------------	----	-----------------	----

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: H 901 A
November 3, 2006

Page 2 of 4

SECTION 4 - FIRST AID MEASURES

INHALATION: Remove affected person to fresh air; provide oxygen if breathing is difficult; if affected person is not breathing, administer CPR and seek emergency medical attention.

SKIN: Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.

EYES: Check for and remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention.

INGESTION: DO NOT induce vomiting; if vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs; seek immediate medical attention. Vomiting may be induced only under the supervision of a physician.

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT (METHOD USED)

15° F (-9.4° C) TCC

FLAMMABLE LIMITS

LEL: 2.6%

UEL: 12.8%

AUTOIGNITION TEMPERATURE: Not determined

NFPA CLASS: **IB**

GENERAL HAZARDS: Product is flammable. Products of combustion include compounds of carbon, hydrogen and oxygen, including carbon monoxide.

EXTINGUISHING MEDIA

Carbon dioxide, water, water fog, dry chemical, chemical foam.

FIRE FIGHTING PROCEDURES

Self - contained respiratory equipment; cool containers to prevent pressure buildup and possible explosion when exposed to extreme heat. Caution - material is flammable!

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers can explode due to buildup of pressure when exposed to extreme heat. Vapors may cause a flash fire or ignite explosively. Vapors may travel a considerable distance to a source of ignition and flash back.

HAZARDOUS COMBUSTION PRODUCTS

Smoke, fumes or vapors, oxides of carbon.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: CAUTION - FLAMMABLE - Evacuate and ventilate area; confine and absorb into absorbent; place material into approved containers for disposal; for spills in excess of allowable limits (RQ) notify the National Response Center (800) 424 - 8802; refer to CERCLA 40 CFR 302 and SARA Title III, Section 313 40 CFR 372 for detailed instructions concerning reporting requirements. Do not discharge into lakes, ponds, streams or public waters.

SECTION 7 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Keep container closed when not in use; protect containers from abuse; protect from extreme temperatures. CAUTION - FLAMMABLE - keep away from all sources of ignition. "Empty" containers may contain residue which may form explosive vapors. Do not weld or cut near empty container that has not been professionally reconditioned. Use non-sparking tools when opening and closing containers. Maintain well ventilated work areas to minimize exposure when handling this material.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS

The use of local exhaust ventilation is recommended to control emissions near the source. Provide mechanical ventilation of confined spaces. Use explosion-proof ventilation equipment.

PERSONAL PROTECTION:

RESPIRATORY PROTECTION: None required while threshold limits are kept below maximum allowable concentrations; if TWA exceeds limits, NIOSH approved respirator must be worn. Refer to 29 CFR 1910.134 or European Standard EN 149 for complete regulations.

PROTECTIVE GLOVES: Neoprene, butyl or nitrile rubber gloves with cuffs.

EYE PROTECTION: Chemical splash goggles. Refer to 29 CFR 1910.133 or European Standard EN166.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Safety eyewash station nearby.

WORK / HYGIENIC PRACTICES: Practice safe workplace habits. Minimize body contact with this, as well as all chemicals in general.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: H 901 A
November 3, 2006

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

VAPOR PRESSURE 185 mm Hg @ 20° C	VAPOR DENSITY (AIR = 1) > 1
SPECIFIC GRAVITY (WATER = 1) 0.826	EVAPORATION RATE (Water = 1) < 1
SOLUBILITY IN WATER Appreciable	FREEZING POINT Not determined
pH Not applicable	APPEARANCE AND ODOR Colorless liquid, characteristic hydrocarbon odor
BOILING POINT 132° F (56° C)	PHYSICAL STATE Liquid
VISCOSITY Approximately that of water	VOLATILE ORGANIC COMPOUNDS (Total VOC's) 6.19 lbs / gal (737 gms / liter)

SECTION 10 - STABILITY AND REACTIVITY

STABILITY UNSTABLE: STABLE: XXX	CONDITIONS TO AVOID: Extreme temperatures, open flames, sparks.
---------------------------------------	---

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers, strong acids.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes or vapors, and smoke may be produced.

HAZARDOUS POLYMERIZATION MAY OCCUR: WILL NOT OCCUR: XXX	CONDITIONS TO AVOID: None
---	---------------------------

SECTION 11 - TOXICOLOGICAL INFORMATION

Hazardous Ingredients	CAS #	LD50 of Ingredient (Specify Species and Route)	LC50 of Ingredient (Specify Species)
Toluene (a,b,c,d,e)	108-88-3	5000 mg / kg Oral - rat	7525 ppm / 4H Inhalation - mouse
Petroleum distillate, aliphatic	64742-89-8	Not determined	Not determined
Ethyl acetate (a,b,c)	141-78-6	6100 mg / kg Oral - rat	45,000 mg / kg / 2H Inhalation - mouse
Methyl ethyl ketone (a,b,c)	78-93-3	3400 mg / kg Oral - rat	8000 ppm / 8H Inhalation - rat
Isopropyl alcohol	67-63-0	5840 mg / kg Oral - rat	22,500 ppm / 4H Inhalation - rat
Acetone (b,c)	67-64-1	9750 mg / kg Oral - rat	16,000 ppm / 4H Inhalation - rat

SECTION 12 - ECOLOGICAL INFORMATION

No data are available on the adverse effects of this material on the environment. Neither COD nor BOD data are available. Based on the chemical composition of this product it is assumed that the mixture can be treated in an acclimatized biological waste treatment plant system in limited quantities. However, such treatment should be evaluated and approved for each specific biological system. None of the ingredients in this mixture are classified as a Marine Pollutant.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of in accordance with Local, State, and Federal Regulations. This product may produce hazardous vapors in a closed disposal container creating a dangerous environment. Refer to "40 CFR Protection of Environment Parts 260 - 299" for complete waste disposal regulations. Consult your local, state, or Federal Environmental Protection Agency before disposing of any chemicals. Do not flush to sanitary sewer or waterway.

SECTION 14 - TRANSPORT INFORMATION

PROPER SHIPPING NAME: Paint related material

DOT HAZARD CLASS / Pack Group: 3 / II
REFERENCE: 49 CFR 173.150, .173, .242
UN / NA IDENTIFICATION NUMBER: UN 1263
LABEL: FLAMMABLE LIQUID
HAZARD SYMBOLS: F
Hazard Identification Number (HIN): 33

Note: Transportation information provided is for reference only. Client is urged to consult CFR 49 parts 100 - 177, IMDG, IATA, EC, United Nations TDG, and WHMIS (Canada) TDG information manuals for detailed regulations and exceptions covering specific container sizes, packaging materials and methods of shipping.

